



FEATURES

- Premium model with monopitch roof and solid, reinforced double frame profiles for greater wind stability
- **∀** Ball bearing double sliding door with cylinder lock
- Glazing with twin-wall polycarbonate glazing for soft light and better insulation properties
- Mixed glazing: Roof in PCG 10 mm and large panes of safety glass, crystal clear (TG) approx. 3 mm in the sides
- Roof with unique slide-in technology always in 10 mm PCG panes.
- Anodised or powder-coated aluminium profiles for lasting protection against corrosion
- 2 sizes from approx. 7.8 and 11.5 m²
- \checkmark Incl. side windows, top windows, gutter + 2 rainwater downpipes

2.95 m 2.67 m 2.95 m 3.93 m 2.95 m 3.93 m 2.95 m 3.93 m 3.

TECHNICAL DATA

House type:	Greenhouse
Classification:	Special model
Sizes:	2
Glazing:	PCG approx. 10 mm; mixed glazing: TG approx. 3 mm + PCG approx. 10 mm in roof
Fixing technique:	Double frame profiles with screwed Aluminium strips
Colours:	Anodised aluminium or white powder-coated
Side windows Upper window:	3 1 (7800) or 2 (11500)
Outer dimensions:	B 2.67 x T 2.95 m (7800); B 3.93 x T 2.95 m (11500)
Eaves height:	1.87 m
Door dimensions:	

